

Advanced IP Phone with 3 lines & HD voice

- TI TITAN chipset and TI voice engine
- 3 VoIP accounts, 132x64 graphic LCD
- HD Voice: HD Codec, HD speaker, HD handset
- 2xLAN, PoE, headset, expansion module



Yealink SIP-T26P is an advanced IP phone which designed for maximum productivity and efficiency in the everyday business environment. It is equipped with the leading TI TITAN chipset, offers high definition voice quality through TI voice engine, HD handset, HD speaker and HD codec (G.722). Built-in 10 DSS keys for programmed as the IP-PBX features like BLF/BLA, intercom, call pickup etc. Six navigation keys and four soft keys help you using the phone easily. Ten dedicated functional keys provide you with direct access to the functions for audio and call control. Moreover, SIP-T26P has the rich external interfaces including 2xLAN, PoE, headset and expansion module ports.

Enterprise HD IP Phone

SIP-T26P

Phone Features

3 VoIP accounts, hotline, emergency call
Call waiting, call transfer, call forward
Hold, mute, flash, auto-answer, redial
3-way conference, DND, speed dial
XML Phonebook search/import/export
Black list, call history (100 entries)
Volume adjustment, ring tone selection
Tone scheme, System log
Multi-language (more than 20)
Supports up to 6 expansion modules

IP PBX System Integration

Dial plan, dial-now
SMS, Voicemail, MWI
BLF/BLA, intercom, paging
Call park, call pickup
Distinctive ringtone

Codecs and Voice Features

Wideband codec: G.722
Narrowband codec: G.711, G.723.1,
G.726, G.729AB
VAD, CNG, AEC, PLC, AJB, AGC
Full-duplex speakerphone with AEC

Network Features

SIP v1 (RFC2543), v2 (RFC3261)
NAT Traversal: STUN mode
DTMF: In-Band, RFC2833, SIP Info
Proxy mode and peer-to-peer SIP link mode
IP Assignment: Static/DHCP/PPPoE
TFTP/DHCP/PPPoE client
Telnet/HTTP/HTTPS server
DNS client
NAT/DHCP server

Management

FTP/TFTP/HTTP/PnP auto-provision
Configuration: browser/phone/auto-provision
Direct IP call without SIP proxy
Dial number via SIP server
Dial URL via SIP server

Security

HTTPS (server/client)
SRTP (RFC3711)
Transport Layer Security (TLS)
VLAN (802.1 pq), QoS
Digest authentication using MD5/MD5-sess
Secure configuration file via AES encryption
Phone lock for personal privacy protection
Admin/user configuration mode

Physical Features

TI TITAN Chipset
132x64 graphic LCD
45 keys including 13 programmable keys
1xRJ9 (4P4C) handset port
1xRJ9 (4P4C) headset port
2xRJ45 10/100M Ethernet ports
1XRJ12 (6P6C) expansion module port
Power adapter: AC 100~240V input
and DC 5V/1.2A output
Power over Ethernet (IEEE 802.3af)
Power consumption: 1.6~2.6W
Net weight: 1.05KG
Dimension: 273x204x42MM
Operating humidity: 10~95%
Storage temperature: up to 60°C

Package Features

Qty/CTN: 5 PCS
N.W/CTN: 7.87KG
G.W/CTN: 9.00KG
Measurement: 0.073CMB
Carton Meas: 470x287x222MM

Certifications

