

Colour Touch Panel Adds Convenience to Business Communication



The Panasonic KX-HDV330 is a multi-functional business IP phone equipped with a colour touch panel for intuitive operation.

KX-HDV330 

Key Features

Colour TFT Touch Panel

4.3-inch Colour LCD

The KX-HDV330's colour LCD gives you a visual understanding of various function-related information, while the touch panel enables easy operation.



Easy confirmation of BroadSoft UC-one presence.





Key Features

Bluetooth®



A wireless headset can be used with the KX-HDV330 to enable smooth and easy response to incoming calls.



Expandable Function Key

The KX-HDV330 comes standard with a total of 24 flexible function keys. Together with the optional expansion module, this provides up to 224 function keys.



Option Expansion Module KX-HDV20

Basic Features

HD Voice Quality

The KX-HDV330 incorporates HD SONIC features, such as full duplex, acoustic echo cancellation, and packet loss concealment, in its hardware and software to maximise voice quality and wideband communication performance.

Up to 12 Lines, 2 x Gigabit Ethernet & PoE

Featuring Gigabit Ethernet for comfortable communication, a single unit can connect to as many as twelve lines. PoE compatibility also eliminates the need for an AC adaptor.

Specifications



White

Black

KX-HDV330

Audio Features

- HD voice
- Wideband codec: G.722
- Narrowband codec: G.711a-law, G.711μ-law, G.729a
- DTMF: In band, Out band (RFC2833), SIP INFO
- Full duplex speakerphone
- CNG, VAD, PLC, AEC

IP Features

- 12 SIP accounts
- IP version: IPv4, IPv6
- NAT traversal (STUN / Rport (RFC3581) / Port Punching)
- Embedded web server
- QoS (Layer 3 ToS DSCP / 802.1p / Q tagging (VLAN))

Phone Features

- Anonymous call (CLIR), Anonymous call rejection
- Call forward, Call hold, Call transfer, Call waiting
- Caller ID (CLIP, CNIP), Caller ID blocking
- Distinctive ring
- Do not disturb
- Ring selection
- Local phonebook (Up to 500 numbers)
- LDAP / XML Remote phonebook
- Blacklists (Up to 30 lists)

Management

- Auto provisioning (SIP PnP / DHCP option / Redirection server)
- Export current active settings
- Automatic firmware upgrade
- Reset to factory default, Reset to carrier default, Reboot

Interface

- Gigabit Ethernet port (2 x 10/100/1000 Mbps)
- Headset port (RJ9)
- EHS Supported
- PoE (IEEE 802.3af)
- Optional Expansion Module interface (Up to 5 units)

Display / Indicator

- 480 x 272 pixel 4.3 - inch colour TFT LCD with touch panel
- LCD backlight
- 1 LED for Ringer, Message waiting and Missed call indication

Others

- Built-in Bluetooth®
- Wall mount (Include)
- Power consumption (PoE): 3.4 W
- Power consumption (AC adaptor): 3.4 W
- Operation environment: 0°C - 40°C / 20% - 80% (Non condensing)
- Dimensions (W x D x H mm): 195 x 190 x 209 (High position)
195 x 184 x 188 (Low position)
- Weight: 850 g

BROADSOFT
Compatible

- Basic Call Feature
- Missed Calls Display
- N-Way Conference

- Busy Lamp Field
- Call Centre
- Call Park Notification

- Click to Call
- Feature Key Synchronisation
- Shared Call Appearance

- Broadsoft Xsi
- BroadSoft Presence
- BroadSoft Xsi Phonebook

Important

-Safety precaution: Carefully read the operating instructions and installation manual before using this products.

- The Bluetooth word mark and logos are trademarks or registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Panasonic Corporation is under license.
- Some models will be available to limited countries.
- The images shown of the base unit display and light are composite images.
- Weights and dimensions are approximate.
- Design and specification subject to change without notice.
- These products may be subject to export control regulations.

DISTRIBUTED BY :

Panasonic®